

Street Stock 4 Wheel Drive Truck Pull
AUGUST 2, 2018 - 7:00 p.m.

Sponsored by
Warren County Farmers' Fair Association &
OK Auto 4WD & Tire, 2621 State Route 57
Stewartsville, N.J. 08886, (908) 454-6973.

REGISTRATION AND INFORMATION

Or

Registration and Rules Online at www.ok4wd.com
Rules subject to change.

Truck pull is limited to 70 TRUCKS

- A pre-registration fee of **\$20.00** is required and can be paid **ONLY at OK AUTO 4WD and TIRE** before the day of the pull.
- Registration on the day of the pull will be up until 5:00 p.m. sharp! and the fee will be \$40.00.
- Weigh-ins & Inspections will start at 4:00 p.m. through 6:00 p.m. in the fenced in area next to the roadway on Stryker Road.
- Mandatory Drivers Meeting at 6:30 p.m.!
- All vehicles will enter arena from that area.

CLASSES:

1x. Under 7000 lbs. Gas Daily Driver

1. Under 6500 lbs. Gas Street Stock

2. Under 6500 lbs. Gas Street Modified

3. Under 8500lbs. Diesel Work Stock

4. Under 6500 lbs Gas Modified

5. Under 8500 lbs. Diesel Modified

GENERAL RULES

1. All participants at every event must sign a waiver understanding that they are entering a pulling contest at their own risk and that they will not bring suit against the Warren County Farmers' Fair Association, Inc. , its directors, OK Auto 4-Wheel Drive and Tire, Inc., and sponsors from any and all responsibility or liability for injury or damages, and

- also, release and agree to indemnify the Warren County Farmers' Fair Association, Inc., OK Auto 4-Wheel Drive and Tire, Inc., against any damage claim, legal proceeding or judgment arising out of the transportation, or exhibition of the listed participant at the said Fair, and further agree to hold the said Warren County Farmers' Fair Association, Inc., OK Auto 4-Wheel Drive and Tire, Inc., harmless from any claim or suit for injury, damage or blame resulting from the participation in this event.
2. Each driver and truck may register only once in each class. Maximum 2 classes.
 3. Driver must have a valid driver's license and must be at least 18 years of age.
 4. Vehicle must have a current state inspection sticker and license for Classes.
 5. All drivers must wear a D.O.T. helmet. Helmet must be **fastened**. It is mandatory that open body vehicles have a 4 point roll bar securely fastened to frame.
 6. All vehicles be equipped with a minimum of one (1) lb. Halon type fire extinguisher, fully charged, in working condition and convenient to operator.
 7. Seat belts are required to be worn.
 8. All vehicles must have a 4-Wheel hydraulic brake system in good working condition.
 9. Vehicles must have a solid fire wall and floor. Only holes allowed are that for brakes, clutch, transmission controls and wiring. No gas tanks or batteries allowed in cab of vehicle unless factory installed.
 10. All vehicles must be in a safe working condition and be operated in a safe manner at all times.
 11. All vehicles must pass tech inspection before hooking to sled. If presiding Head Official(s) thinks a vehicle is unsafe, official(s) have the right not to allow vehicle to pull. The tech inspection area closes 6:00 p.m. sharp!!
 12. All engine fans must be shrouded.
 13. NO smoking while on track.
 14. All participants must drive vehicle onto track and into position for hook up under its own power and must leave track under its own power unless for breakage.
 15. Track officials will have the option to check pullers for weight and rule violations at any time during the event.

16. Only the DRIVER will be allowed in a vehicle when it is being towed or driven while in the pit area or track. No rider(s) in or on any vehicle while in the pit area or track, to include tow vehicles, competing vehicles, tow back and maintenance equipment of any kind. When the pulling vehicle's motor is running, the driver must be in the driver's seat. NO EXCEPTIONS.
17. All vehicles must be in neutral or park while being hooked or unhooked from the sled. Driver must raise both hands while hooking and unhooking from sled.
18. No one is allowed on the track except for track officials and participant when vehicle is under the green flag. Track is defined as the area within 35 feet in any direction of the contest boundaries, including the run off area at the finish end of the track.
19. Vehicles will not start pulling until both flagmen have green flags showing. Vehicles must stop immediately upon signal of red flag from flagmen.
20. All pulls must start with a tight chain, no jerking of any kind is permitted and vehicle must remain within boundaries of the track or the puller will be disqualified.
21. Puller will be allowed a total of two (2) attempts within the 75 feet mark to start the sled. Test puller may drop six (6) positions.
22. Mandatory drivers' meeting will be held before starting of event at 6:30 p.m. SHARP!
23. A participant will be disqualified for either emotional or physical reasons by Head Officials, or track official(s). Example: Recklessness, drugs, or drinking alcoholic beverages. Any driver or any of his/her crew incapacitated to an intoxicating agent, and/or drugs, will be barred from the event.
24. If a vehicle and/or driver is disqualified for any reason, no refund of entry fee will be given.
25. All participants will, at the time of tech inspection, pick pulling positions through a drawing.
26. Trophies and gift certificates will be presented to the first, second and third class winners.
27. Dual wheels only acceptable in Diesel classes.
28. Please read disclaimer on registration form before signing as it has been changed.

AWARDS

1st place, trophy, ribbon and gift certificate for \$50.00

2nd place, trophy, ribbon and gift certificate for \$35.00

3rd place, trophy, ribbon and gift certificate for \$25.00

In addition to the awards above a cash prize will be awarded in modified classes and they will be awarded as follows:

Street Gas Modified

1st place – \$100 cash prize

2nd place - \$60 cash prize

3rd place - \$40 cash prize

Diesel Modified

1st place – \$300 cash prize

2nd place - \$200 cash prize

3rd place - \$100 cash prize

Gas Modified

1st place – \$300 cash prize

2nd place - \$200 cash prize

3rd place - \$100 cash prize

ALL VEHICLES SUBJECT TO TECH COMMITTEE APPROVAL.

Each truck is required to have a minimum 2-1/2 lbs. ABC fire extinguisher securely mounted in the cab and within reach of the driver.

1x Under 7000lbs Gas Daily Driver Rules ***NEW CLASS FOR 2018***

Two wheel drive and Four wheel drive – NO DIESEL

7000 lbs. weight is with driver

The purpose of class is for stock trucks.

See also General Rules, which apply for this and all classes.

1. **Ballast** – No hanging front weights. No hidden weight. No weight in cab. Any and all ballast must be in the bed of the truck only, and securely fastened.
2. **Batteries**- Factory location only, securely fastened.
3. **Body** – Tailgate not required. The body must be the OEM truck body. The body must retain full sheet metal. Metal aftermarket hoods are permitted. Fiberglass hoods are permitted with a sheet metal or aluminum skin shield underneath of at least .060" thick. The hood must be closed and securely

latched while vehicle is hooked to sled. The complete OEM firewall and OEM floor pan is mandatory. A factory installed pickup bed or commercial style aftermarket bed must be installed.

4. **Brakes** – Four wheel hydraulic functional brakes are mandatory.

5. **Chassis** – Limited to OEM - “ONE TON” rating maximum.

6. **Cooling**- The radiator must be in the stock location and of at least stock size.

7. **Credentials** – Valid Inspection, Registration Card, Insurance Card, & Driver’s License.

8. **Driver Restraint** – The OEM restraint system is mandatory and must be worn.

9. **ENGINE, DRIVETRAIN, and SUSPENSION must be STOCK.** NO suspension modifications. NO internal engine mods. NO cylinder head modifications. NO camshaft modifications. NO intake manifold modifications. No forced induction unless it came stock.

10. **Exhaust** –Manifolds must be stock and Must be street legal.

11. **Fire Extinguisher** – Required.

12. **Fuel** – Pump Gas Only.

13. **Hitch** – Must be a receiver-style OEM factory designed towing hitch or standard factory bumper hitch. No special pulling hitches or modified receivers – no bracing. Hooking point must be the rear-most of the vehicle and must be rearward of stock tailgate location. Hitch must be horizontal to the ground and stationary in all directions. Hitch Height from ground may not exceed 26 inches. Hooking point must have a minimum 4 inch inside opening for the sled to hook. NO CLEVISES. No vertical hitches. Hitch/ Hook point must be in place at scale weigh-in.

14. **Interior** – A complete interior, including dashboard, door panels, headliner, etc. is mandatory. Two matching seats are mandatory. All factory controls (lights, signals, horn, wipers, etc.) must be retained and operative.

16. **Street Equipment** – Complete headlight and taillight assemblies (all) are mandatory and must be operative. Complete OEM windshield and windows are mandatory. Windows must be operative per factory specifications; that is, they must open and close via OEM electrical or mechanical means.

GAS CLASS RULES

1. Under 6500lbs Gas Street Stock

2. Under 6500lbs Gas Street Modified

4. Under 6500lbs Gas Modified

1. Hook point must be no more than 6 inches in, from rear of frame. Hook point/drawbar for 4WD vehicles cannot exceed 26" in height before, during or after the pull.
2. Drawbar must be rigid in all directions and must be in center line of vehicle. No chains, cables, or double clevis for hitching device.
3. Drawbar must be equipped with a steel hitching device no more than 2" by 2" square or 2" round stock: and with a 4" round hole.
4. Hitch device must be securely attached at rear of frame. No pintle hitches (must be one piece of steel). Street stock must have class 3 type hitch or a bumper that is of class 3 capacity.
5. Tires must be D.O.T. approved in all classes except Gas Modified. Cut tires are allowed only in Gas Modified class. D.O.T tires cannot be altered in any way.
6. Suspension may be blocked only in modified classes. Blocks must be securely fastened. Must be stock suspension or lifted suspension with stock configuration.
7. Air bags must be deflated with air hoses disconnected in stock classes.
8. Weights in front allowed in modified classes. Weights must be securely fastened. Automatic disqualification if weights fall off. No weights and /or ballast inside cab. Loose weights and/or ballast are not allowed. Weights and/or weight bars cannot exceed 60 inches from center of front axle towards front of vehicle in Modified Class. Vehicles will be weighed with registered driver. VEHICLE MUST BE

REGISTERED BEFORE WEIGHING WITH WEIGHTS ALREADY ON.

Weights in bed of truck must be securely fastened.

9. Body, hood, bed and fenders must meet O.E.M. specifications on class 1-3. Flatbeds must be NJ street legal.
10. One four barrel carburetor: aluminum intake allowed. No rams or cross rams allowed. Street Modified and Modified class may use non-original engine. No blowers or super charger. Classes 4 and 5 must have drive shaft loop, U-Joint shield, and an external kill switch for engine.
11. Headers permitted but no larger than 3" opening. Only classes 2 and 4 may run open exhaust. If engine is not stock, blow-proof bell housing on trucks with standard blanket on automatic transmission may be required. If required, automatic transmission must be covered 360 degrees with an approval blow-proof blanket. Blanket must cover from back of engine block to where the tail shaft bolts to the main housing of the transmission. S.F.I. approved transmission shields will be permitted.

3. Under 8500lbs Diesel Work Stock Rules

WORK STOCK

The Work Stock (WS) Class is designed for daily-driven, on the road pickup trucks (full-bodied diesel pickup truck). **Valid DOT registration and license plates are mandatory.** The vehicle may be two or four-wheel drive.

Regulations:

1. **Ballast:** Ballast is permitted. Hanging front weights are prohibited. Ballast may be added in the bed of the truck. If used, ballast must be securely fastened to the bed of the truck. Final decisions rest with the tech official.
2. **Batteries:** The batteries must be securely mounted. **They may not be located in the driver compartment or forward of the radiator core support.**
3. **Body:** The Body must be an OEM truck body, including the full bed floor. The body must retain all original sheet metal. Metal After-market hoods are permitted, Fiberglass is prohibited. The hood must be closed and securely latched while the vehicle is hooked to the sled. The complete OEM firewall and OEM floor pan is mandatory.
4. **Brakes:** Four-wheel hydraulic brakes are mandatory and must be functional.
5. **Chassis:** The OEM chassis is mandatory. The engine must be in the OEM location for the body being used. The vehicle must retain the full OEM chassis. Wheel tubs, back-half conversions, tube chassis, etc., are prohibited.
6. **Cooling System:** Radiators must be in the stock location and must be of at least stock size.
7. **Credentials:** All drivers must have a valid state driver's license, inspection, registration, & current insurance in hand at time of event sign up.
8. **Driveline:** An OEM transmission and transfer case are mandatory. They must have been an option on a one-ton or smaller pickup.
9. **Driver Restraint System:** The OEM restrain system is mandatory and must be worn.
10. **Engine:** The engine is limited to a stock-appearing, OEM make-specific compression ignition engine. Nitrous Oxide is prohibited along with other oxygen extenders as well as the use of propane is

also prohibited. All system components MUST be removed from the truck.

11. **Exhaust:** The exhaust must exit rearward of the driver's compartment. Stacks exiting through the hood or fender well are prohibited.
12. **Fire Extinguisher** - Is required
13. **Fuel:** The fuel must be pump #1 or #2 diesel only. Soy/Bio-diesel fuel is permitted. Off-road diesel fuel is prohibited.
14. **Fuel Injection Pump:** The fuel injection pump is limited to a stock appearing, OEM engine model-specific pump only. The use of multiple high-pressure common-rail fuel pumps is prohibited. Power Stroke engines with a single factory turbo may utilize a second HPOP. Pumps from different years in the same engine model may be interchanged.
15. **Fuel System:** The OEM fuel tank is mandatory and must be used. Racing fuel cells are prohibited and must be removed from the vehicle.
16. **Harmonic Balancer:** All engines turning 4500 RPM and higher must be equipped with a harmonic balancer or damper meeting SFI Spec 18.1.
17. **Hitch:** The hitch must be a receiver-style hitch; reinforcements are permitted. Reinforcements must not extend forward of the centerline of the rear axle. Trick hitches are prohibited. The hooking point must be in the rear most point on the vehicle and must be rearward of the stock location of the tailgate. The hitch must be horizontal to the ground and stationary in all directions. Bumpers may be notched or removed. The hitch's height from the ground may not exceed 26 inches. The hooking point must have a minimum 4 inch inside diameter opening for the sled hook. No clevis or vertical hitches allowed.
18. **Interior:** A complete interior, including dashboard, door panels, headliners, etc., is mandatory. Two matching front seats are mandatory. Aftermarket seats are permitted; they must be fully upholstered. All factory controls (lights, signals, horn, windows, wipers, etc.) must be retained and be operative. The use of hand throttle controls is prohibited.
19. **Rear End:** Non-OEM rear end housings are prohibited. It must have been an option on a one-ton or smaller pick up. Rear axle bolts must be covered by a cap or shield.

20. **Steering:** The vehicle must retain the full, original OEM steering gear. The vehicle must retain the original OEM power steering assistance, if it was so equipped. Additional stabilizers are permitted. Non-OEM power assist methods are prohibited.
21. **Street Equipment:** Complete headlight and taillight assemblies (all) are mandatory and must be operative. Complete OEM windshield and windows are mandatory. Windows must be operative per factory specifications; that is, they must open and close via OEM electrical or mechanical means.
22. **Suspension, Front:** The upper mounting point for strut assemblies must be in the factory location. Adjustable caster/camber pillow ball mounts are permitted. The lower control arm may be strengthened provided factory-mounts are permitted. The lower control arm may be strengthened provided factory-mounting points to chassis are maintained. The lower mounting point for the strut assembly may be modified for improved caster or camber. Strut tower braces, lower tie bars, sway bars, and limit straps are permitted. Traction bars and devices are permitted.
23. **Suspension, Rear:** An OEM-style suspension is mandatory. Lowering or raising the vehicle height with suspension modifications is permitted. Traction bars and devices are permitted. They must be bolt-on only; welds are permitted for attachment to frame or axle housing. All OEM suspension mounting points must be retained and used. Sway bars, limit straps, and camber kits are permitted. The rear suspension must maintain a minimum compression shock travel of one inch compression. Stops may be adjustable. All rear suspensions must use at least one working shock absorber per wheel. Airbag spring assistance is permitted; airbag compressors must be disconnected, no in-cab controls.
24. **Tires:** The tires must be DOT street tires. Cut tires are prohibited.
25. **Tow Vehicles:** Tow vehicles are prohibited.
26. **Transfer Case:** Non OEM transfer cases are prohibited. The transfer case must have been an option on a one-ton or smaller pick-up truck.
27. **Transmission, Automatic:** Non-OEM transmissions are prohibited. All vehicles with engines running 4500 RPM or more using an automatic transmission must be equipped with a transmission shield meeting SFI Spec 4.1 and must be labeled accordingly. A blanket-type shield is permitted; it must be appropriately labeled as meeting SFI Spec 4.1 and it must extend from the rear of the block to the front of

- tail housing with a minimum of six inch overlap where it is fastened. All non-blanket-type shields must incorporate two (or one, per manufacturer's instructions) 3/4 inch by 1/8 inch straps that bolt to the shield on each side and pass under the transmission pan unless the transmission pan is labeled as meeting SFI Spec 4.1. All vehicles with engines running 4500 RPM or more and using an automatic transmission must be equipped with a flex plate meeting SFI Spec 29.1 and be covered by a flex plate shield meeting SFI Spec 30.1.
28. **Transmission, Manual:** Non-OEM transmissions are prohibited. A clutch meeting minimum SFI Spec 1.1 or 1.2 is mandatory on all vehicles with engines running 4500 RPM or more. All manual transmissions must be clutch assisted. Sequential shifters are prohibited. All vehicles with engines running 4500 RPM or more equipped with a manual transmission must have a flywheel shield labeled as meeting minimum SFI Spec 6.3 or greater. Applications for which an SFI Spec flywheel shield is not available may use a properly attached SFI 4.1 or 4.2 blanket that completely covers the bell housing it must be attached to the block and extend rearward to the transmission with a minimum six inch overlap where it is fastened.
29. **Turbocharger:** The turbocharger is limited to a stock-appearing, OEM/Factory make-specific charger only. 6.4/ liter Power Stroke engine may utilize the factory twin-turbo configuration.
30. **Water Injection:** Water injection is prohibited. All system components must be removed from the truck.
31. **Wheelbase:** The vehicle must retain the original factory wheelbase and track width.

5. Under 8500lbs DIESEL MODIFIED Rules

Weight: 8500lbs. Maximum, with driver.

REGULATIONS:

1. **Ballast:** Ballast is permitted. Hanging weights must not extend more than 60 inches from the centerline of the front axle.

2. **Batteries:** The batteries must be securely mounted. They may not be located in the driver compartment or forward of the radiator core support.
3. **Body:** The body must be the OEM truck body, including the full bed floor. The body must retain full sheet metal. Metal after-market hoods are permitted. Fiberglass is prohibited. The hood must be closed and securely latched while the vehicle is hooked to the sled. The complete OEM firewall and complete OEM floor pan is mandatory.
4. **Brakes:** Working minimum of front hydraulic brakes required.
5. **Chassis:** The OEM chassis is mandatory. The engine must be in the OEM location for the body used. The vehicle must retain the full OEM chassis. Wheel tubs, back-half conversions, tube chassis, etc are prohibited.
6. **Cooling System:** Radiators must be in the stock location and be of at least stock size.
7. **Credentials:** All drivers must have a valid state drivers license.
8. **Driveline:** OEM transmission and transfer cases are mandatory. They must have been an option on a one-ton or smaller pickup.
9. **Driver Restraint System:** The OEM restrain system is mandatory and must be worn.
10. **Driveshaft Loops:** All trucks must have at least six inch u-joint shields around the rear u-joint constructed of at least 1/4 inch steel or 3/8 inch aluminum that will safely contain the u-joint and the end of the rear shaft. All the shields must be securely mounted to the vehicle. Any front shaft u-joint that is visible from the side of the truck must be shielded to contain the u-joint and the end of the shaft.
11. **Engine:** The engine block must have been available as a factory option on a one-ton or smaller pickup truck. Blocks must circulate coolant freely. The use of concrete or other block fillers is prohibited. Electric fans are permitted. Alternators must be present and powered via the crankshaft. Water pumps must be present, but may be powered electrically. NITROUS OXIDE and other oxygen extenders as well as the use of PROPANE is also prohibited. All system components MUST be removed from the truck. No RPM limit, aftermarket intake manifolds allowed.
12. **Exhaust:** All vehicles must be equipped to direct exhaust upward. Two 3/8 inch diameter bolts must be installed through the exhaust

pipe in a cross pattern within one inch of each other as close to the turbo as is practical.

13. Fire Extinguisher: A fire extinguisher is required.

14. Fuel: The fuel must be pump #1/#2 diesel only. Soy/Biodiesel fuel is permitted. Off-road diesel fuel is prohibited.

15. Fuel Injection Pump: The fuel injection pump is limited to a stock-appearing, OEM engine make-specific pump only. Dual high-pressure common-rail fuel pumps or HPOPS are permitted. The P7100 injection pump, if equipped, may utilize either a stock or agricultural governor.

16. Harmonic Balancer: All engines turning 4500 RPM and higher must be equipped with a harmonic balancer or damper meeting SFI Spec 18.1.

17. Hitch: The hitch must be a receiver-style hitch; reinforcements are permitted. Reinforcements must not extend forward of the centerline of the rear axle. Trick hitches are prohibited. The hooking point must be the rear-most pint on the vehicle and must be rearward of the stock location of the tailgate. The hitch must be horizontal to the ground and stationary in all directions. Bumpers may be notched or removed. The hitch's height from the ground may not exceed 26 inches. The hooking point must have minimum 4 inch inside diameter opening for the sled hook. No clevis allowed.

18. Master Cutoff: All trucks must be equipped with a master cutoff. A sled and driver-operated spring-loaded emergency air shutoff is mandatory. The cable must terminate into a two inch diameter steel ring.

19. Rear End: Non-OEM rear-end housings are prohibited. The rear end must have been an option on a one-ton or smaller pick up. Rear axle bolts must be covered by a cap or shield.

20. Steering: Additional stabilizers are permitted to OEM steering system. Hydraulic steering is permitted.

21. Suspension, Front: The factory suspension configuration must be retained. The upper mounting pint for strut assemblies must be in the factory location. Adjustable caster/camber pillow ball mounts are permitted. The lower control arm may be strengthened provided factory-mounting points to chassis are maintained. The lower mounting point for the strut assembly may be modified for improved caster or camber. Strut tower braces, lower tie bars, sway bars, and

limit straps are permitted. Traction bars and devices are permitted. The final decision rests with the NADM Technical Department.

22. **Suspension, Rear:** An OEM-style suspension is mandatory. Traction bars and devices are permitted; they must be bolt on only; welds are permitted for attachment to frame or axle housing. Control arms may be strengthened or replaced, provided all original mounting points are retained. Strut tower braces, lower tie bars, sway bars, limit straps, and camber kits are permitted. The rear suspension may be bolted solid to eliminate travel.
23. **Tires:** The tires must be DOT street tires. Cut tires are prohibited.
24. **Transfer Case:** Non-OEM transfer cases are prohibited. It must have been an option on a one ton or smaller pickup
25. **Transmission, Automatic:** Non-OEM transmissions are prohibited. All vehicles with engines running 4500 RPM or more and using an automatic transmission must be equipped with a transmission shield meeting SFI Spec 4.1 and must be labeled accordingly. A blanket-type shield is permitted; it must be appropriately labeled as meeting SFI Spec 4.1 and it must extend from the rear block to the front of tail housing with a minimum six inch overlap where it is fastened. All non-blanket-type shields must incorporate two (or one, per manufacturers instructions) 3/4 inch by 1/8 inch straps that bolt to the shield on each side and pass under the transmission pan unless the transmission pan is labeled as meeting SFI Spec 4.1. All vehicles with engines running 4500 RPM or more and using an automatic transmission must be equipped with a flex plate meeting SFI Spec 29.1 and be covered by a flex plate meeting SFI Spec 30.1.
26. **Transmission, Manual:** Non-OEM transmissions are prohibited. A clutch meeting minimum SFI Spec 1.1 or 1.2 is mandatory on all vehicles with engines running 4500 RPM or more. All manual transmissions must be clutch assisted. Sequential shifters are prohibited. All vehicles with engines running 4500 RPM or more and equipped with a manual transmission must have a flywheel shield labeled as meeting a SFI Spec 6.3 or greater. Applications for which and SFI Spec flywheel shield is not available may use a properly attached SFI 4.1 or 4.2 blanket that completely covers the bell housing; it must be attached to the block and extend rearward to the transmission with a minimum six inch overlap where it is fastened
27. **Turbocharger:** The vehicle is limited to a single turbocharger; the inducer bore on the compressor housing may be no larger than 2.8

inches measured at the smallest diameter area of the compressor wheel. A bushing may be used to downsize the compressor housing ahead of the wheel. If a bushing is used, it must be round metallic, at least 3/4 inch long, mounted within 0.050 inch of the compressor wheel, and the inside diameter of the bushing may not exceed the 2.8 inch limit. Bushings must be securely fastened to the compressor housing. The inlet will be measured using a 2.85 inch plug or internal calipers. A stock map width enhancement (MWE) groove is allowed. No MWE groove will be allowed that has a width greater than 1/4 inch. All provisions allowing air to the wheel other than via the bore and the MWE groove are prohibited

28. **Water Injection:** Water injection is prohibited. All system components must be removed from the truck

29. **Wheelbase:** The vehicle must retain the original unaltered factory wheelbase and track width. Front dual-wheel spacers may be used only with accompanying positive-offset dually style wheels.

Any truck not meeting the rules will be placed in the Exhibition class as long as all safety rules are met. The Exhibition class has no pay out.

RULES SUBJECT TO CHANGE!
PLEASE CONTACT OK AUTO 4WD & TIRE FOR QUESTIONS!